

# It's just 5 simple steps to configure the perfect leg




Follow these five simple steps in configuring your wheel chair legs and the resulting unique configuration identifier is ALL you will need to place your order.

### Sample Configuration Identifier

## STEP 1

Select the manufacturer from the list and put the code into box 1



Base	CODE
Invacare	IN
Quickie	QI
Quantum	QA
Other	OT

**SEAT** 

## STEP 2

Select the seat from the list and put the code into box 2



Innovation In Motion

**SEAT** 

Standard	IS
Motion Concepts Standard	MS
Permobil C350	PC

Invacare	2	
	Rehab Seat (track on seat rail)	RS
	Solara/Compass (round seat rails)	SC
Quickie		
	Iris	IR
	Quickie 2	QT
	Rehab Seat (removable legrest hange	RR r)
Quantu	m	
	Synergy	SY
	Basic Rehabilitation (square seat rail no track)	BR
PDG		
	Fuse	FU
	Eclipse	EC
Gunnel		
	Standard	GS

CODE

CODE



## STEP 3

Enter the code for Left Leg, Right Leg or Both Legs.



#### **NUMBER OF LEGS** CODE

RLRight Leg Left Leg LL **Both Legs** BL

## STEP

Enter the code for the type of upper leg you want.




#### UPPER LEG TYPE

70 Degree 01 02 90 Degree Knee Axis 03 Knee/RHI 04

CODE

Enter the code for the type of lower leg you want.




#### **LOWER LEG TYPE**

CODE 10 Standard Ankle Adjustable 11 Ankle/Foot Adjustable 12

NOTE: If you are ordering two legs which are different from one another, then each leg must have its own identifier when you order.

Example of coding for two different legs on same system



## Accessories: Gel

FOOT PLAT	e Covers	LEG HANGER CAP	KNEE PROTECTOR WRAP
Bolt-on cover with wood base fits standard adult footplates.	Bolt-on center-mount cover w/wood base fits most manufacturer's regular sizes	Velcro® closure covers hangers when legrest is not in use.	Knee protector wrap fits knee bend on fixed frame manual chairs with 3/4" to 1" tubing.
	TÎÎ		
GFPC	GFPCS	LHC (NS)	KPR (NS)
	KNEE PROTECT		
For elevating legrests; 1 1/4"	For elevating legrests; 7/8" thick	For swing away legrests; 11/4" thick	For swing away legrests; 7/8" thick
KBE	KBET	KBM	KBMT
CALF PANEL	LEG WRAP	LEG PROTECTOR PAD	HEEL LOOP Cover
Split panel allows use of swing away legs without removal; fits 16-20" wide seat.	Velcro® closure fits 70 degree swing away legrests	3 ½ x 12" pad and hardware; fits 7/8" or 1" tubing legs	Velcro® closure with three gel sections enhancing proper fit.
GHS-2	LPW	FLGP	HLC-3

## Accessories: Miscellaneous

STUMP	STUMP	Knee	
Support	SUPPORT PAD	ADDUCTORS	
Clamps to 7/8" or 1" round tubing – see pad on right.	7" x 7" gel pad and cover	Swing-away; complete with 3" X 5" gel pad. Clamps to 7/8" or 1" tubing. Black; comes in pair.	
FRSS	FRSS77	FRAB	

## **Special Instructions**

Please use the box below to print clearly any special instructions or customization which you may be requesting.

